



## SKF PFT 25 TR bearing units

Bearing No. PFT 25 TR

Bore Diameter	25 mm
Width	34,1 mm
d	25 mm
Da	60 mm
A1	2 mm
B	34,1 mm
G	8 mm
H	95 mm
H1	– mm
J	76 mm
L	71 mm
N	8,7 mm
T	21,8 mm
A2	9 mm
Weight	0,28 Kg
Basic dynamic load rating (C)	14 kN
Basic static load rating (C0)	7,8 kN
Housing material	Pressed steel
D <sub>a</sub> min.	56 mm
A <sub>1</sub>	2 mm
A <sub>2</sub>	9 mm
B <sub>4</sub>	5 mm
s <sub>1</sub>	19.8 mm
Basic dynamic load rating C	14 kN
Basic static load rating C <sub>0</sub>	7.8 kN
Fatigue load limit P <sub>u</sub>	0.335 kN

PFT 25 TR Bearing 2D drawings and 3D CAD models



## IOR Bearing Manufacturing Co.,Ltd

Limiting speed	4300 r/min
Mass bearing unit	0.28 kg
Thread grub screw G <sub>2</sub>	M6x0.75
Hexagonal key size for grub screw N	3 mm
Recommended tightening torque for grub screw	4 N · m
Recommended diameter for attachment bolts, mm G	8 mm
Recommended diameter for attachment bolts, inch G	0.3125 in